



# Decorscreed

## Decorative Industrial Floor Screed

### DESCRIPTION

Decorscreed provides a hard wearing, impact and abrasion resistant decorative floor surface. Decorscreed is a blend of solvent free epoxy resins, curing agents and graded coloured quartz aggregates. The components of the product have been carefully selected to provide Decorscreed with excellent application properties.

### USES

Decorscreed product has been designed for use in a wide range of industrial and commercial environments such as pharmaceutical, food and beverage, packing and light manufacturing, hospitals, reception areas, laboratories, retail premises and custodial buildings.

### ADVANTAGES

- **Durable** Hard wearing surface resistant to both impact damage and abrasion
- **Seamless** Provides a joint-free, easy to clean surface
- **Slip Resistant** lightly textured profile provides a good non slip surface to pedestrian traffic
- **Decorative** Attractive multi-coloured floor system
- **Thickness** 4-5mm giving no interference with existing levels
- **Low odour** Non tainting and suitable for use in sensitive areas

### SLIP RESISTANCE

#### Slip Resistance Value – BS 7976-2 : 2002

4S Rubber Slider Wet	46
4S Rubber Slider Dry	59
TRL Rubber Wet	50
TRL Rubber Dry	94

### CHEMICAL RESISTANCE

Decorscreed is resistant to a wide range of chemicals. Specific data is available on request from the Technical Services Department.

### COLOURS

Decorscreed is available in a range of blended colours, offering the designer a wide choice, subject to status. Contact our Technical Services Department for details.

### TEMPERATURE

Decorscreed should not be applied at temperatures below 13° C and above 40° C. A combination of low temperature and high humidity can effect the application and curing of this product.


### APPLICATION

Decorscreed is installed by Conren's in-house specialist contractors.

## COLOUR SELECTION




SMOKE




CORN




RUSSET




BRICK



FOREST



LAWN



MIDNIGHT



SKY

## DISPOSAL

All tools and equipment should be cleaned with Conren solvent cleaner immediately after use. Spillage should be absorbed with sand or sawdust and disposed of in accordance with statutory regulations.

## STORAGE

Shelf life at least 12 months if stored in original containers between 10° C and 25° C

## PRECAUTIONS

For further information on our precautions please see the MSDS.

## Technical Service and Quality Assurance

All information provided in this leaflet is based on results obtained from our own experience and testing which is given in good faith. The information is provided without guarantee as the user will be deemed to have satisfied themselves independently of the suitability of Conren's product for their own particular purpose. Conren Limited cannot be held responsible for any errors as a result of any incorrect information being provided.



[www.conren.com](http://www.conren.com)

Conren Limited. Unit 1, The Bridge Business Centre,  
Ash Road South, Wrexham Industrial Estate,  
Wrexham. LL13 9UG

Tel: +44 (0) 1978 661 991  
Fax: + 44 (0) 1978 664 664  
E-mail: [info@conren.com](mailto:info@conren.com)