

Description:

IMPRIDUR is an epoxy resin based sealer used as hardener in building supports with cracks. It is also used as primer for epoxy based renders.

Uses:

It is used supports found in industrial plants, in the food industry, car garages, docks, warehouses, garages, parking areas, factories, bottling plants, packaging plants, commercial shops and premises, etc.

Features & benefits:

EXCELLENT FLUIDITY.GOOD PENETRATION INTO THE SUPPORT.

Surface preparation:

The background of application must be clean, sound, free of grease, wax, oil, stains, with no trace of floor finishing products.

Application:

- Mix 2 parts of component "A" to 1 part of component "B" in weight. .
- On new supports: apply with a woollen roller, paint brush or gun directly onto the concrete support. In interiors, one coating is sufficient.
- On old supports, apply at least two coatings with a woollen roller and leave to dry 4 to 6 hours in between each coating.

TechnicalFeatures:

Density: component "A": 0.95 Kg/L \pm 0.05 component "B": 0.95 Kg/L \pm 0.05
Viscosity: 12 \pm 2 s.
Colour/s: Transparent.
Aspect: Smooth, hard and brilliant finish.
Open time: 6 Hours.

Coverage:

6 to 8 m² per l.

Clean up:

Clean using our solvent DISOLVENTE EPOXI.

Storage:

It is recommended to store this product for 2 years in tightly closed original packages.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.

Packaging:

Available in packs of:

.: 2.25 L

15 L

Health and safety advice :

R10 -- Flammable

R20 -- Harmful by inhalation

S9 -- Keep container in a well-ventilated place

S16 -- Keep away from sources of ignition - No smoking

S24/25 -- Avoid any inhalation, contact with skin and eyes. Wear suitable protective clothing and gloves

S33 -- Take precautionary measures against static discharges



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.