

Description:

IMPRILAIS is a primer that is soluble in water. It is used to ensure strong adhesion to RELAIS and is made of high quality synthetic resins in water scattering.

Uses:

It is used as primer so as to ensure proper adherence to RELAIS plastic render.

Features & benefits:

ADHERENCE IS IMPROVED.IT OFFERS A COLOUR BACKGROUND FOR RELAIS.

Surface preparation:

The background of application must be clean, free of grease, oil, dust, loose particles, by being compact, dry or slightly damp.

Application:

- Mix the content of each package thoroughly before using the product.
- Apply using a paint brush or roller.
- Dilute in water up to 50%(maximum) and then apply one single coating.
- Leave to stand for at least 8 hours before applying RELAIS.

TechnicalFeatures:

Density: 1.67 Kg/L \pm 0.05
Viscosity: 50.000 \pm 10.000 mPa.s
-: Easy application and great efficiency.
-: Easy paint brush application and great penetrating power.
-: Application in interiors and exteriors
Colour/s: Blanco, crema, marrón claro and oscuro, gris, limón and verde.

Coverage:

10 m2 per kg.

Clean up:

Clean using large amounts of water.

Storage:

It is recommended to store this product for 2 years in tightly closed original packages.

Packaging:

Available in packs of:

.: 6 Kg
25 Kg

Health and safety advice :

R43 -- May cause sensitisation by skin contact



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.