

Description:

LASTOIS FH-CV is a one component product, elastomer and plastic resin based with additives and high water-resistant pigments. It is used as external waterproofing covering.

Uses:

It is ideal for waterproofing and decorating in facades. In certain cases, it also used for waterproofing on passable decks. It is also applied as finishing coat for LASTOIS CAPA INTERMEDIA.

Features & benefits:

EXCELLENT WATERPROOFING PROPERTIES. INCREASED ELASTICITY. OPTIMUM ADHERENCE. COLOUR DURABILITY IS ENSURED.

Surface preparation:

The background should be clean, grease, oil and dust free, providing a sound and compact surface with no trace of efflorescence and chippings.

Application:

- Mix thoroughly to a uniform consistency before use
- Priming is done using IMPRIMAIS M.U. (on old and contaminated walls).
- Once dry, apply the first coating of LASTOIS CAPA INTERMEDIA using a woollen or threaded paint roller.
- It can be then reinforced with VELAIS fibreglass using a roller so as to fully embed it by overlapping up to 2 cm., by avoiding any ridges or air bags.
- Once dry, apply LASTOIS FH-CV using an average porous sponge roller (so as to obtain a textured effect and to smoothen the overlapping layers). In order to achieve maximum waterproofing results, it is recommended to apply a last coating of ACRILAIS TRANSLUCIDA.
- LASTOIS FH-CV can be also used without LASTOIS CAPA INTERMEDIA, as a regular elastomeric paint.
- Once dry, apply LASTOIS FH-CV using an average porous sponge roller (so as to obtain a textured effect and to smoothen the overlapping layers). In order to achieve maximum waterproofing results, it is recommended to apply a last coating of ACRILAIS TRANSLUCIDA.

Technical Features:

Density: 1.25 Kg/L \pm 0.05
Viscosity: 65.000 mPa.s \pm 15.000
Resistance to traction: >2 N/mm²
Solubility: it is possible to mix with water.
Application temperature: 5 to 30 °C

Coverage:

1.8 m² per kg in 300 micron coating.

Clean up:

Tools must be cleaned with plenty of water before the product sets. Once dry, clean mechanically.

Storage:

It is recommended to store this product for 2 years in tightly closed original packages in a cool dry place.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



waterproofing lastois fh-cv

waterproof render based on elastomeric resins

Packaging:

Available in packs of:

Verde, Marron and Rojo Teja: 20 Kg

5 Kg

Blanco, Crema, Gris and Negro: 20 Kg

5 Kg

Health and safety advice :

R43 -- May cause sensitisation by skin contact



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is not possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es