

### Description:

Waterproofing paint based on an aqueous dispersion of vinyl copolymers, made for indoors and outdoors surfaces decoration and protection.

### Uses:

In facades, inner courtyards, party walls, balconies, large fortified towers, domes, etc.  
Onto fibrocement boards, cement mortar renders, gypsum, plaster, etc by priming previously.

### Features & benefits:

\* EXCELLENT WEATHERPROOFING \* WATERPROOF \* RESISTANT \* DECORATIVE \* ANTICARBONATION PROPERTIES \*

### Surface preparation:

Must be clean, without the presence of greases, oils, dust and loose particles, appearing perfectly dry.

### Clean up:

With plentiful clean water while the paint is fresh.

### Application

- Mix the contents of the bottle well, manually or with electric mixer low rpm 300-500 rpm.
- Apply With a brush, roller or spray.
- Apply the first coating by diluting up to 10 to 15% in weight in water.
- Once the first coating is dry(after at least 12 hours), apply a second or more coatings without diluting, in the same interval of time as for the first coating.
- The support must be clean, free of grease, dust or loose parts, being compact and perfectly dry, in case of using IMPRIMAIS MU primer.

### Packaging:

Available in packs of:

Glossy: White.

5 Kilos

20 Kilos

Smooth: Browns,reds, moss-greens, blues and greens.

5 Kilos

25 Kilos

Smooth: Ivory colour, ochre, salmon, coral and greys.

5 Kilos

### Technical features:

Aspect	smooth, matte and glossy.
Colour/s	white and colors according to color chart.
Density	1,54 Kg./Liter $\pm$ 0,05 (varies depending on color).
Dry for repainting	12 Hours /50 microns dry film/20°C/65% of H.R.
Dry upon touching	1 Hour /50 microns dry film/20°C/65% of H.R.
Totally dry	24 Hours /50 microns dry film/20°C/65% of H.R.
Viscosity	40.000 $\pm$ 10.000 mPs.a at 20°C

### Coverage:

Smooth: 3 sqm per kg; Glossy 3 to 5 sqm per kg

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña  
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es



acrilais

DURABLE AND HIGH RESISTANCE WATERPROOFING PAINT FOR OUTDOORS

Edition: 6

04/2010

Technical department

25 Kilos

Smooth: Whites

5 Kilos

25 Kilos

**Storage:**

2 years, in their original packagings and properly closed, never under 5°C temperature, stored in a cool and a dry place.

**Health and safety advice:**

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña  
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es