



deais ecológico standard

ECOLOGICAL RELEASE-AGENT WITH VEGETAL BASE FOR UNIVERSAL USE

Edition: 1 12/2010

Technical department

Description:

Ecological release-agent in liquid shape in vegetal base without solvents for concrete prefabs and construction in general.

Uses:

On industries dedicated to the manufacturing on prefab concrete and construction in general. It can be applied to all types of metallic moulds, wood, plastic, polyester, elastomers, polystyrene, etc

Technical features:

Aspect	Oily liquid
Colour/s	Amber
Density	0,93±Kg./Lt. ± 0,05
Odour	Characteristic

Features & benefits:

ECOLOGICAL EASY TO USE* DOES NOT EMIT VAPOUR*
PROTECT MOULDS* DOES NOT SPOT* IT ALLOWS HIGH
QUALITY SURFACES* AVOIDS THE MORTAR AND
CONCRETE ADHERENCES TO THE MOULDS*

Surface preparation:

The surface must be pretty cleaned, free of greases, without rust, concrete wastes or dust of cement in order to avoid spots on concrete.

Clean up:

With soap and water.

Coverage:

30 to 40 sqm/ LT according with support and use.

Application

-Apply without dilute.

-It must be applied by brush, roller or spray can on the mould having special care avoiding parts free of release-agent.

-The product avoids the adherence of the concrete with the moulds.

-It does spot neither concretes nor mortars.

Packaging:

Available in packs of:

- 1 Litre 20 Packages per box
- 5 Litre 4 Packages per box
- 25 Litre
- 200 Litre

Storage:

1 year in their original packages and tightly closed.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es