



Description:

Oily liquid specially formulated for moulds made of wood and metal.

Uses:

It is used in all types of moulds made of wood or metal both in work and prefab industry. It can be used on concretes placed by traditional methods as vibrated, self-compacting, etc.

Technical features:

Aspect	Oily liquid
Colour/s	Amber translucent
Density	0,85 kg/l

Features & benefits:

* EASE TO APPLYING* PROTECTS THE MOULDS*
SOLUBLE IN GAS OIL AND OTHER HYDROCARBONS* HIGH
PERFORMANCE*

Surface preparation:

The surface of the moulds must be cleaned, free of dust, particles, wastes of mortars or concretes and dry.

Clean up:

The tools used can be cleaned with cleaning solvent

Coverage:

5 to 10 sqm/lt not diluted, diluted 15 to 30 sqm/l

Application

- Shake strongly the content of the package before using.
- Apply preferably as the product is provided.
- Soluble in gas oil and other hydrocarbons.
- The application must be done with brush, roller, spray can before placing the metallic armour.
- The concretes which going to be painted on or cladding with mortars must be washed with plenty of water and brushed with brushes to remove wastes of release-agents.

Packaging:

Available in packs of:

5 Litre 4 Packages per box
25 Litre

Storage:

1 year in their original packages, protected from the weather and stored in cool and dry places.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es