



emplais exteriores

POWDER PRODUCT USED FOR OUTDOOR PLASTERING

Edition: 6 10/2010

Technical department

Description:

Powder product based in cement to be mixed with water so as to form a plastic paste used for plastering, whitewash cracks and chippings on walls and ceilings, both in interiors and exteriors.

Uses:

Used so as to eliminate irregularities on surfaces to be painted afterwards (in interiors and exteriors), to level rendered supports as well as to eliminate cracks and fissures.

Features & benefits:

*EASY APPLICATION EXCELLENT *WORKABILITY
*STRONG HARDNESS *

Surface preparation:

The background of application must be clean and perfectly dry, free of grease, saltpeter and dust, being compact and firm.

Technical features:

Adherence	> 5 kg/cm ²
Capillarity	< 1,5% at 60 min
Colour/s	white
Compressive resistance	> 150 kg/cm ²
Flexural strength resistance	> 45 kg/cm ²
Mass of density	1,900 g/cc. ± 0,05
Open time	> 45 min.
Powder density	0,85 g/cc. ± 0,05
Water absorption	35 ± 3%
Water retention	> 97%

Clean up:

Clean with large amounts of water.

Coverage:

1 sqm per kg in layer of 1 mm.

Application

- To be mix with water.
- Apply it by trowel or spatula on thin layer.
- Once EMPLAIS EXTERIORES is dry apply TEAIS Paint on it as decorative coating.
- Before painting on the plaster let it dry at least 50 hours since the last coat.

Packaging:

Available in packs of:
OUTDOOR

- 1 Kilos 24 Packages per box
- 4 Kilos
- 20 Kilos

Storage:

It is recommended to store this product for 2 years in its tightly closed original packages protected against bleakness.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es