

Description:

Based-lime stucco for indoor and outdoor decorative finishes. Paste product that once applied presents a sleek finish with veined marble imitation.

Uses:

Decoration of housings, shops, offices, cafes, hotels, very suitable for interior decoration of any construction.

Features & benefits:

* EXCELLENT ESTHETIC * IDEAL FOR DECORATION * EASY APPLICATION * MARBLE EFFECT * GREAT ADHESION ON VARIOUS HOLDERS *

Technical features:

Colour/s
Composition
Density
Open time
pH value
Temperature of work

Surface preparation:

Must be very smooth, free of oil stains, greases, fungus, dust, etc.

Clean up:

With plentiful clean water while the material is fresh. After hardened it will can only be removed by mechanical means.

Coverage:

1,6 m² per sqm

Application

-Stiring the content of the container in order to homogenize the product properly.
-On the smooth surface based on ESTUCAL or another lime based or cement based render.
A coating smaller than a millimetre of ESTUCAL is applied with a stainless trowel.
Once dry, sand with "double zero (00)" sander.

- After that another layer smaller than 1 millimetre and once flatted it will be polished with the edge of the trowel pressing hardly over ESTUCAL.

-The suitable dry between layers has to be 24 hours more or less in order to obtain a completely dry.

-In outdoors can be protected with ESTURBIL and in wet indoor or outdoor can be protected with ESTUPROT.

-The supports have to be free of moisture. They can be painted in which case a sand will be done, and if the paint is firm and in good conditions, is enough with sanding and the dust elimination.

Packaging:

Available in packs of:

4 Kilos

19 Kilos

Storage:

2 years in their original packagings, properly closed stored in a fresh and dry place, well protected from the weather.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es