

### Description:

Proticer is a liquid product applied as a paving protector for before grouting ceramic. The product facilitates the subsequent cleaning of the tiles avoiding that the grout material remains embedded in them. The product remains as a definitive protection on the support once it is finished cleaning.

### Uses:

Proticer is applied to facilitate the cleaning of the tiles after grouting. The product remains as a protection on the tiles, giving a satin look.

### Features & benefits:

\* EASY TO APPLY \* MAKES EASY CLEANING OF THE GROUT \* REMAIN AS A PROTECTION AFTER CLEANING \* SLIGHTLY SATIN SURFACE EFFECT\*

### Surface preparation:

The surface of application of the tiles must be clean and dry, free of dust or loose particles.

### Clean up:

The tools used will be cleaned with Disoluais N.

### Technical features:

Colour/s	transparent
Density	1,0 Kg/L. $\pm$ 0,03 at 20°C.
Solid content in volume	> 15%
Temperature of work	5 to 30°C
Totally dry	12 hours

### Coverage:

4-5 m<sup>2</sup> per l.

### Application

- Shake to homogenize well the contents of the package.
- PROTICER is applied using a paint brush, gun or spray in the recommended coverage of 4-5 m<sup>2</sup>/l approximately.
- The surface of application must be clean and dry.
- In case of more absorbent areas than others, repeat the application, to obtain a homogeneous surface.
- Apply before grouting and leave to dry completely. Apply without diluting.
- While the grouting is done, the surface is cleaned and finally the cleaning of the entire surface is finished.

### Packaging:

Available in packs of:

0,75 Litre 6 Packages per box

5 Litre 4 Packages per box

### Storage:

Two years in its original containers protected from the elements, without sudden changes of temperature.

### Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña  
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es