

Description:

RETARDOIS is a liquid additive of setting-time for mortars and concretes.

Uses:

RETARDOIS is suitable for delaying the setting-time, with hot weather, when a big quantity of concrete to place is required, when it requires to avoid the concreting joints, when it transported over long distances, with bad conditions for placing, when it requires to increase the workability-time, etc.

Features & benefits:

CONTROLLED DELAY OF SETTING-TIME WITHOUT LOSSES AND RESISTANCES*

Surface preparation:

It is not necessary.

Clean up:

With plenty of water.

Application

-Shake the content of the package in order to homogenize it before using.
-RETARDOIS must be added to water but in a proportion less than 1,5% in cement weight used (maximum dose must be 0,40 litres per cement sack). It is recommended a previous test in order to achieve the setting-time delay required.

Packaging:

Available in packs of:

- 1 Litre 20 Packages per box
- 5 Litre 4 Packages per box
- 25 Litre

Storage:

In their original packages, tightly closed, in a dry and cool place for 3 years.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

Technical features:

Colour/s	Colourless.
Density	1,05 Kg/L. (+-) 0,05 at 20°C
PH	7 aprox.
Solid content	25% aprox.
Viscosity	11 ± 1 sec to 20°C. Ford coat: 4mm.

Coverage:

From 0,125 to 0,400 l per cement sack.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is not possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es